

Since 1960, Stucchi is one of the leading manufacturers of quick disconnect couplings, with a wide variety of sizes and port configurations ranging from 1/8" to 2" suitable for some of the most demanding applications.

To compliment our core product we offer the FCP range which includes check, ball and flow control valves. In two, three and multi position, steel and stainless steel from 1/8" through to 5", BSP, SAE and NPT, Metric and ISO port configurations.



BD - RF



Flow Control: **Bi-Directional, Reverse flow check**
 Material: **Carbon Steel**
 Available Size: **1/4" to 1 1/2"**
 Port: **BSP, NPT**
 Operating Pressure: **350 bar**
 Temperature range: **-20 +100 °C (depending on body and seal material)**

BIR



Valving Style: **Poppet**
 Interchange: **ISO 7241 'A'**
 Sealing description: **Nitrile NBR**
 Available sizes: **From 1/4" to 2"**
 Operating Pressure: **Up to 350 bar**
 Flow rate: **Up to 1000 L/min**
 Material / Treatment: **Carbon steel / Cr3**
 Connection under pressure: **Allowed (only PC version)**

GR



Valving style: **Flat face**
 Interchange: **Stucchi profile**
 Available sizes: **From 3/8" to 1"**
 Operating pressure: **Up to 350 bar**
 Flow rate: **Up to 378 L/min**
 Material: **Brass & high strength carbon steel**
 Connection system: **Lever**
 Connection under pressure: **Both side, easy connection**

657 Dundas Road,
 Forrestfield WA 6058
 Forrestfield – sales@holdfast.com.au
 Broome – salesnw@holdfast.com.au
 Naval Base – sales2@holdfast.com.au
 Phone Number: 1300 465 332



Stucchi®



BALL VALVES

COUPLINGS

CHECK VALVES

GE2 SERIES



Number of Ports: **2**
Material: **Available in carbon steel and stainless steel**
Available Sizes: **¼ to 1"**
Port: **NPT, BSP, SAE, Flange**
Operating Pressure: **Up to 500 bar**
Temperature range: **-60 + 230 °C (dependent on body and seal material)**

GE3 SERIES



Number of Ports: **3**
Port Type: **L and T**
Material: **Available in carbon steel and stainless**
Available Sizes: **¼ to 1"**
Port: **NPT, BSP**
Operating Pressure: **Up to 400 bar**
Temperature range: **-60 + 230 °C (dependent on body and seal material)**

M/P SERIES



Valving style: **Poppet**
Interchange: **ISO 7241 'A'**
Sealing description: **Nitrile NBR**
Available sizes: **From 1/4" to 1"**
Operating Pressure: **Up to 350 bar**
Flow rate: **Up to 200 L/min**
Material / Treatment: **Carbon steel / Cr3**

IRC SERIES



Valving style: **Poppet**
Interchange: **Nordic interface**
Sealing description: **Nitrile NBR**
Available Sizes: **From 1/4" to 1"**
Operating Pressure: **Up to 600 bar**
Flow rate: **Up to 378 L/min**
Material / Treatment: **Carbon steel / Cr3**
Connection under pressure: **Allowed (only PC version)**

FIRG SERIES



Valving style: **Flat face**
Interchange: **ISO 16028**
Sealing description: **Nitrile NBR**
Available Sizes: **From 1/4" to 2"**
Operating Pressure: **Up to 300 bar**
Flow rate: **Up to 1000 L/min**
Material / Treatment: **Carbon steel / Cr3**

IFR SERIES



Valving style: **Flat face**
Interchange: **ISO 5676**
Sealing description: **Nitrile NBR**
Available Sizes: **3/8"**
Operating Pressure: **Up to 150 bar**
Flow rate: **Up to 23 L/min**
Material / Treatment: **High strength carbon steel**

VUZ SERIES



Available Sizes: **From 1/8" to 2"**
Operating Pressure: **Up to 400 bar**
Flow rate: **Up to 1000 L/min**
Material / Treatment: **Carbon steel / Cr3**

ACCESSORIES



Available: **Caps & Plugs, Parking Stations, Seal & Repair Kits, Anodised Colour Coding**



WARNING A defect, a wrong choice or an improper use of products, can cause injury to persons, animals and objects. Connect under pressure products are suitable to be connected under residual (static) pressure. Never connect or disconnect with dynamic pressure (e.g. pump on). Make sure that the medium used is compatible with seal and material as indicated for each series. In case of doubt please contact Stucchi Technical Support. The interchangeability is mentioned under the assumption that the manufacturer of the considered products has not changed any dimension.

It is **MANDATORY** to read and closely follow the instructions. Last updated version always apply at time of installation, see latest written Instructions on Stucchi website (www.stucchi.it) before selecting or using Stucchi products.



Stucchi®



HOLDFAST FLUID POWER 1300 465 332