

HOLDFAST

FLUID POWER



Stucchi®



Since 1960, Stucchi is one of the leading manufacturers of quick disconnect couplings, with a wide variety of sizes and port configurations ranging from 1/8" to 2" suitable for some of the most demanding applications.

To compliment our core product we offer the FCP range which includes check, ball and flow control valves. In two, three and multi position, steel and stainless steel from 1/8" through to 5", BSP, SAE and NPT, Metric and ISO port configurations.



Available Size: **From DN6 to DN50**
 Operating pressure: **Up to 400 bar**
 Ends: **BSP - NPT**
 Material/treatment: **316L**
 Connection system: **Screw**
 Profile: **Straight & 90 degree**



Valving style: **Poppet**
 Interchange: **ISO 7241 'B'**
 Sealing description: **FKM (Viton®)**
 Available sizes: **From 1/8" to 1"**
 Operating pressure: **Up to 250 bar**
 Flow rate: **Up to 200 l/min**
 Material / Treatment: **316L**



Available Sizes: **From 1/8" to 2"**
 Operating Pressure: **Up to 400 bar**
 Flow rate: **Up to 1000 L/min**
 Material / Treatment: **316L**

657 Dundas Road,
 Forrestfield WA 6058
 Forrestfield – sales@holdfast.com.au
 Broome – salesnw@holdfast.com.au
 Naval Base – sales2@holdfast.com.au
 Phone Number: 1300 465 332

SOLUTIONS

STAINLESS



Stucchi®



Number of Ports: **2**
 Material: **Available in carbon steel and stainless steel**
 Available Sizes: **¼ to 1"**
 Port: **NPT, BSP, SAE, Flange**
 Operating Pressure: **Up to 500 bar**
 Temperature range: **-60 + 230 °C (dependent on body and seal material)**



Number of Ports: **3**
 Port Type: **L and T**
 Material: **Available in carbon steel and stainless**
 Available Sizes: **¼ to 1"**
 Port: **NPT, BSP**
 Operating Pressure: **Up to 400 bar**
 Temperature range: **-60 + 230 °C (dependent on body and seal material)**



Valving style: **Poppet**
 Interchange: **ISO 7241-1 A**
 Available sizes: **From 1/4" to 2"**
 Operating pressure: **Up to 350 bar**
 Flow rate: **Up to 1000 L/Min**
 Material: **316L**
 Connection system: **Single acting sleeve**
 Connection under pressure: **Not allowed**



Valving style: **Poppet**
 Interchange: **ISO 14541**
 Available sizes: **From 1/4" to 1 1/4"**
 Operating pressure: **Up to 450 bar**
 Flow rate: **Up to 378 L/Min**
 Material: **316L**
 Connection system: **Screw**
 Connection under pressure: **One side**



Valving style: **Poppet**
 Interchange: **VVS Interchange**
 Available Sizes: **From 1/4" to 2"**
 Operating Pressure: **Up to 650 bar**
 Flow rate: **Up to 750 L/min**
 Material: **316L**
 Connection system: **Screw**
 Connection under pressure: **One side**



Valving style: **Poppet**
 Interchange: **Nordic interface**
 Sealing description: **FKM (Viton®)**
 Available sizes: **From 1/4" to 1"**
 Operating pressure: **Up to 300 bar**
 Flow rate: **Up to 378 l/min**
 Material / Treatment: **316L**



Valving style: **Flat face**
 Interchange: **ISO 16028**
 Sealing description: **FKM (Viton®)**
 Available sizes: **From 1/8" to 2"**
 Operating pressure: **Up to 350 bar**
 Flow rate: **Up to 1000 l/min**
 Material / Treatment: **316L**



Valving style: **Poppet**
 Interchange: **With similar couplings**
 Sealing description: **Nitrile NBR**
 Available sizes: **From 3/4" to 2"**
 Operating pressure: **Up to 207 bar**
 Flow rate: **Up to 1100 l/min**
 Material / Treatment: **316L**
 Connection under pressure: **Allowed**



A defect, a wrong choice or an improper use of products, can cause injury to persons, animals and objects. Connect under pressure products are suitable to be connected under residual (static) pressure. Never connect or disconnect with dynamic pressure (e.g. pump on). Make sure that the medium used is compatible with seal and material as indicated for each series. In case of doubt please contact Stucchi Technical Support. The interchangeability is mentioned under the assumption that the manufacturer of the considered products has not changed any dimension.

It is **MANDATORY** to read and closely follow the instructions. Last updated version always apply at time of installation, see latest written Instructions on Stucchi website (www.stucchi.it) before selecting or using Stucchi products.